



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	50	Hz
Speed	n	1420	RPM
Power consumption	P _e	260	W
Nominal current	I _{nom}	1.2	A
Maximum current	I _{max}	1.8	A
Cos φ		1	
Capacitor		05/400	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	64	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	53	dB(A)
Weight		29.6	Lbs.
Packing dimensions		25.0x25.0x14.2	inch

Fan details


Impeller blades	3
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0.00 in. wg	2970 CFM
-------------	----------



Please note: Picture may deviate from original product

Approval(s)







Wiring diagram

C1 - 1 Phase - Standard - CCW

S0000010695A



Dimensions			
		A01:	20.2 inch
		A03:	22.6 inch
		A13:	6.9 inch
		A14:	13.1 inch
		A29:	1.3 inch
		A30:	4.5 inch
			
VOSTERMANS VENTILATION			
Vostermans Ventilation B.V. Venlo - The Netherlands +31 (0)77 389 32 32 ventilation@vostermans.com		Vostermans Ventilation Inc. Bloomington, IL - U.S.A. +1 309 827 9798 ventilation@vostermansusa.com	
		Vostermans Ventilation Ltd. Co. Shanghai - China +86 21 5290 2889/2899 ventilation@vostermanschina.com	
		Vostermans Ventilation Sdn. Bhd. Tmn Klang Jaya - Malaysia +60 (0)33324 3638 ventilation@vostermansasia.com	