

Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	865	RPM
Power consumption	P _e	640	W
Nominal current	I _{nom}	3.2	A
Maximum current	I _{max}	3.6	A
Cos φ		0.88	
Capacitor		14/400	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Weight		61.7	kg

Fan details



Impeller blades	3
Impeller type	8
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics

0 Pa 19900 m³/h
50 Pa 14300 m³/h



Please note: Picture may deviate from original product

Approval(s)



VOSTERMANS
VENTILATION


Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com


Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram
C1 - 1 Phase - Standard - CCW



Dimensions



A01:	913 mm
A02:	1246 mm
A03:	1246 mm
A04:	182 mm
A05:	8 mm
A06:	1153 mm
A07:	1236 mm
A08:	1286 mm