



Technical data

Voltage	U	120	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1500	RPM
Power consumption	P _e	460	W
Nominal current	I _{nom}	3.9	A
Maximum current	I _{max}	4.4	A
Cos φ		0.97	
Capacitor		20/250	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	77	dB(A)
Sound pressure level (7 m)	L _p (calc.)	66	dB(A)
Weight		16.5	kg
Packing dimensions		635x635x360	mm


Fan details

Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics




Please note: Picture may deviate from original product



Wiring diagram
C2 - 1 Phase - Dual Low voltage - CCW

S0000010696A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions				
				
A01:	518 mm			
A02:	620 mm			
A03:	620 mm			
A10:	6.5 mm			
A11:	420 mm			
A12:	33 mm			
A13:	236 mm			
A14:	327 mm			
A15:	369 mm			

