



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	580	RPM
Power consumption	P _e	1750	W
Nominal current	I _{nom}	8.2	A
Maximum current	I _{max}	11.5	A
Cos φ		0.93	
Capacitor		32/400	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	78	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	67	dB(A)
Weight		290.9	Lbs.

Fan details



Impeller blades	6
Impeller type	12
Impeller system	B
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics

0.00 in. wg 31600 CFM
0.20 in. wg 28200 CFM



Please note: Picture may deviate from original product




No.15460




Wiring diagram

C1 - 1 Phase - Standard Startup Capacitor - CW



Dimensions



A01:	53.9 inch
A02:	67.3 inch
A03:	67.3 inch
A08:	7.0 inch
A09:	0.4 inch
A20:	63.8 inch
A22:	65.0 inch
A26:	73.8 inch