



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	630	RPM
Power consumption	P _e	1750	W
Nominal current	I _{nom}	5.8/3.4	A
Maximum current	I _{max}	6.7/3.9	A
Cos φ		0.75	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		249.3	Lbs.
Packing dimensions		0.7x39.4x39.4	inch

Fan details



Impeller blades	3
Impeller type	12
Impeller system	B
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics

0.00 in. wg	31450 CFM
0.20 in. wg	26350 CFM



Please note: Picture may deviate from original product

Approval(s)




Wiring diagram
C11 - 3 Phase - Y connection - CW



FC fans - High volume

Technical drawing of a square ventilation grille. The drawing shows a square frame with a central circular grille. The grille is composed of horizontal and vertical slats. Dimensions are indicated: A01 is the diagonal length of the square frame, A02 is the width of the square frame, and A03 is the height of the square frame. The central circular grille has a diameter of 100 mm. The drawing is labeled with 'A01', 'A02', and 'A03'.



A01:	50.3 inch
A02:	60.2 inch
A03:	60.2 inch
A08:	7.0 inch
A09:	0.4 inch
A20:	56.7 inch
A22:	63.0 inch
A26:	69.6 inch

