



Technical data

Voltage	U	200-230	V
Phase		1	~
Frequency	f	50/60	Hz
Speed	n	945	RPM
Power consumption	P _e	800	W
Nominal current	I _{nom}	5.8	A
Maximum current	I _{max}	6.4	A
Cos φ		0.6	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		45.7	Lbs.

Fan details


Impeller blades	3
Impeller type	8
Impeller system	G
Impeller material	PG

Control options


Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg 12100 CFM
0.20 in. wg 9950 CFM



Speed control diagram




Please note: Picture may deviate from original product



Wiring diagram


CC03 - 3 Phase - Delta connected + MFD33S --



Article number: P6D92FAM11100FD

Tube mounting fans - ECplus

Dimensions



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com