



Technical data

Voltage	U	200-230	V
Phase		1	~
Frequency	f	50/60	Hz
Speed	n	540	RPM
Power consumption	P _e	1150	W
Nominal current	I _{nom}	8	A
Maximum current	I _{max}	11.0	A
Cos φ		0.62	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		0	
IP Class		IP55	
Weight		302.1	Lbs.

Fan details


Impeller blades	3
Impeller type	12
Impeller system	B
Impeller material	PG

Control options



Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg 29450 CFM
0.20 in. wg 21250 CFM



Speed control diagram



Please note: Picture may deviate from original product

Approval(s)



No.23399



VOSTERMANS
VENTILATION


Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com


Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram
CC14 - 3 Phase - Delta connected Domel AZ + MFD70SHD (CW) - CW




Aln	Dig In 1
10 - 0V	Dig In 1 = NC
0 - 10V	Dig In 1 = 24V



Alarm = 0V
~~Alarm = 24Vdc~~

*US cable

Dimensions



A01:	53.9 inch
A02:	67.3 inch
A03:	67.3 inch
A08:	7.0 inch
A09:	0.4 inch
A20:	63.8 inch
A22:	65.0 inch
A26:	73.8 inch