



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	50	Hz
Speed	n	910	RPM
Power consumption	P _e	590	W
Nominal current	I _{nom}	2.7	A
Maximum current	I _{max}	3.6	A
Cos φ		0.97	
Capacitor		16/400	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	77	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	66	dB(A)
Weight		42.7	Lbs.
Packing dimensions		9.7x39.4x39.4	inch

Fan details


Impeller blades	3
Impeller type	8
Impeller system	G
Impeller material	PG

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0.00 in. wg 10200 CFM
0.20 in. wg 8360 CFM




Please note: Picture may deviate from original product



Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A



Article number: P6E92AAM11100

Tube mounting fans



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com