Article number: P4S45AAE11100

Tube mounting fans

Technical data

Voltage	U	230	V
Phase		1	~
Frequency		50	Hz
Speed		1420	RPM
Power consumption	P_e	320	W
Nominal current	I	1.5	A
Maximum current	I	2.2	A
Capacitor		10/400	µF
Ambient temperature	$T_{amb\ min/max}$	-25...40	°C
Insulation Class		CL.F	
IP Class Fan		IP55	
Sound pressure level	L_p	68	db(A)
Sound pressure level distance		2	m
Weight		12.2	kg
Packing dimensions		510x510x315	mm

Fan details

Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No
Intelligent Fan Drive	Yes

Characteristics

0 Pa	6750 m^3/h
50 Pa	5850 m^3/h



Please note: Picture may deviate from original product

Approval(s)

ErP 2020

Wiring diagram - Fan

AA01 - 1 Phase - Standard - CCW



Dimensions



Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Version 2.5 07Nov2022