

## Technical data

|                               |                          |                 |       |
|-------------------------------|--------------------------|-----------------|-------|
| Voltage                       | U                        | 400-480         | V     |
| Phase                         |                          | 3               | ~     |
| Frequency                     | f                        | 50/60           | Hz    |
| Speed                         | n                        | 600             | RPM   |
| Power consumption             | P <sub>e</sub>           | 1500            | W     |
| Nominal current               | I <sub>nom</sub>         | 2.1             | A     |
| Maximum current               | I <sub>max</sub>         | 2.9             | A     |
| Cos φ                         |                          | 0.9             |       |
| Capacitor                     |                          | -               | μF/V  |
| Ambient temperature           | T <sub>amb min/max</sub> | -13...104       | °F    |
| Insulation Class              |                          | CL.F            |       |
| IP Class                      |                          | IP55            |       |
| Sound pressure level (6.6 ft) | L <sub>p</sub> (meas.)   | 76              | dB(A) |
| Sound pressure level (23 ft)  | L <sub>p</sub> (calc.)   | 66              | dB(A) |
| Weight                        |                          | 283.6           | Lbs.  |
| Packing dimensions            |                          | 102.0x39.4x39.4 | inch  |

## Fan details


|                   |    |
|-------------------|----|
| Impeller blades   | 3  |
| Impeller type     | 12 |
| Impeller system   | B  |
| Impeller material | PG |

## Control options



|                  |     |
|------------------|-----|
| Triac controller | No  |
| Transformer      | No  |
| Frequency drive  | Yes |

## Characteristics

|             |           |
|-------------|-----------|
| 0.00 in. wg | 37500 CFM |
| 0.20 in. wg | 31650 CFM |



## Speed control diagram




Please note: Picture may deviate from original product

## Approval(s)




Wiring diagram



CC01 - 3 Phase - Star connected + MFD40T/95T - -



| Aln     | Dig In 1       |
|---------|----------------|
| 10 - 0V | Dig In 1 = NC  |
| 0 - 10V | Dig In 1 = 24V |



Dimensions



|      |           |
|------|-----------|
| A01: | 53.9 inch |
| A02: | 67.3 inch |
| A03: | 67.3 inch |
| A08: | 7.0 inch  |
| A09: | 0.4 inch  |
| A20: | 63.8 inch |
| A22: | 65.0 inch |
| A26: | 73.8 inch |