Article number: G4D14L4M10238

Galvanised cone fans

Multifan

Technical data

Voltage	U	254/440	V
Phase		3	~
Frequency	f	60	Hz
Speed	n	595	RPM
Power consumption	P_e	1550	W
Nominal current	I_{nom}	4.8/2.8	A
Maximum current	I_{max}	6.2/3.6	A
Cos ϕ		0.81	
Capacitor		-	µF/V
Ambient temperature	$T_{amb\ min/max}$	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		264.0	Lbs.
Packing dimensions		24.4x39.4x39.4	inch

Fan details

Impeller blades	6
Impeller type	12
Impeller system	B
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg	26600 CFM
0.20 in. wg	23200 CFM





Please note: Picture may deviate from original product

Approval(s)

ErP 2026 COMPLIANT

VOSTERMANS VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Version 3.0 22Oct2025

Article number: G4D14L4M10238

Galvanised cone fans

Wiring diagram

C11 - 3 Phase - Y connection - CCW



Article number: G4D14L4M10238

Galvanised cone fans

Dimensions

A01:	54.1 inch
A08:	5.3 inch
A09:	11.6 inch
A19:	58.3 inch
A20:	58.3 inch
A22:	53.4 inch
A26:	65.2 inch
A31:	3.3 inch



Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com