Article number: H4D6302M10100

High Pressure fans

Multifan

Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	1450	RPM
Power consumption	P_e	1650	W
Nominal current	I_{nom}	5.7/3.3	A
Maximum current	I_{max}	6.5/3.8	A
Cos ϕ		0.73	
Capacitor		-	µF/V
Ambient temperature	$T_{amb\ min/max}$	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		56.9	Lbs.
Packing dimensions		43.3x35.4x20.9	inch

Fan details

Impeller blades	6
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg	11250 CFM
0.60 in. wg	9470 CFM



Please note: Picture may deviate from original product

Approval(s)

CE

ErP 2015

VOSTERMANS VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Version 3.0 22Oct2025

Article number: H4D6302M10100

High Pressure fans

Wiring diagram

C11 - 3 Phase - Y connection - CCW



Article number: H4D6302M10100

High Pressure fans

Dimensions

A01:	25.2 inch
A03:	34.1 inch
A07:	28.1 inch
A08:	8.3 inch
A10:	0.4 inch
A14:	16.1 inch



VOSTERMANS VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com