

Technical data

Voltage	U	265/460	V
Phase		3	~
Frequency	f	60	Hz
Speed	n	1140	RPM
Power consumption	P _e	450	W
Nominal current	I _{nom}	1.8/1.1	A
Maximum current	I _{max}	2.0/1.2	A
Cos φ		0.54	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		56.0	Lbs.
Packing dimensions		32.5x32.5x15.6	inch

Fan details


Impeller blades	3
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	Yes
Frequency drive	Yes

Characteristics

0.00 in. wg	6150 CFM
-------------	----------




Please note: Picture may deviate from original product

Approval(s)

Motor approval


Wiring diagram
C11 - 3 Phase - Y connection - CCW



Dimensions			
		A01:	27.9 inch
		A03:	32.7 inch
		A13:	9.1 inch
		A14:	16.3 inch
		A29:	1.1 inch
		A30:	4.5 inch
			
VOSTERMANS VENTILATION			
Vostermans Ventilation B.V. Venlo - The Netherlands +31 (0)77 389 32 32 ventilation@vostermans.com		Vostermans Ventilation Inc. Bloomington, IL - U.S.A. +1 309 827 9798 ventilation@vostermansusa.com	
		Vostermans Ventilation Ltd. Co. Shanghai - China +86 21 5290 2889/2899 ventilation@vostermanschina.com	
		Vostermans Ventilation Sdn. Bhd. Tmn Klang Jaya - Malaysia +60 (0)33324 3638 ventilation@vostermansasia.com	