



Technical data

|                               |                          |                |       |
|-------------------------------|--------------------------|----------------|-------|
| Voltage                       | U                        | 240            | V     |
| Phase                         |                          | 1              | ~     |
| Frequency                     | f                        | 60             | Hz    |
| Speed                         | n                        | 1130           | RPM   |
| Power consumption             | P <sub>e</sub>           | 205            | W     |
| Nominal current               | I <sub>nom</sub>         | 0.9            | A     |
| Maximum current               | I <sub>max</sub>         | 1.2            | A     |
| Cos φ                         |                          | 0.96           |       |
| Capacitor                     |                          | 05/400         | μF/V  |
| Ambient temperature           | T <sub>amb min/max</sub> | -13...104      | °F    |
| Insulation Class              |                          | CL.F           |       |
| IP Class                      |                          | IP55           |       |
| Sound pressure level (6.6 ft) | L <sub>p</sub> (meas.)   | 47             | db(A) |
| Sound pressure level (23 ft)  | L <sub>p</sub> (calc.)   | 36             | db(A) |
| Weight                        |                          | 34.5           | Lbs.  |
| Packing dimensions            |                          | 28.3x28.3x15.7 | inch  |

Fan details

|                   |    |
|-------------------|----|
| Impeller blades   | 8  |
| Impeller type     | 3  |
| Impeller system   | C  |
| Impeller material | PP |

Control options

|                  |     |
|------------------|-----|
| Triac controller | Yes |
| Transformer      | Yes |
| Frequency drive  | No  |

Characteristics

|             |          |
|-------------|----------|
| 0.00 in. wg | 3060 CFM |
|-------------|----------|



Please note: Picture may deviate from original product

Approval(s)



Wiring diagram  
C1 - 1 Phase - Standard - CW

S0000010695A



**VOSTERMANS**  
VENTILATION

Vostermans Ventilation B.V.  
Venlo - The Netherlands  
+31 (0)77 389 32 32  
ventilation@vostermans.com

Vostermans Ventilation Inc.  
Bloomington, IL - U.S.A.  
+1 309 827 9798  
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.  
Shanghai - China  
+86 21 5290 2889/2899  
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.  
Tmn Klang Jaya - Malaysia  
+60 (0)33324 3638  
ventilation@vostermansasia.com

