



Technical data

Voltage	U	240	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1550	RPM
Power consumption	P _e	420	W
Nominal current	I _{nom}	1.8	A
Maximum current	I _{max}	2.0	A
Cos φ		0.99	
Capacitor		20/250	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		3.7	Lbs.

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0.00 in. wg 4770 CFM
0.20 in. wg 3910 CFM




Please note: Picture may deviate from original product

Approval(s)



Wiring diagram
C3 - 1 Phase - Dual High Voltage - CCW

S0000010697A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions				
				
A01:	20.4	inch		
A02:	24.4	inch		
A03:	24.4	inch		
A10:	0.3	inch		
A11:	16.5	inch		
A12:	1.3	inch		
A13:	9.3	inch		
A14:	12.9	inch		
A15:	14.5	inch		

