



Technical data

Voltage	U	200-230	V
Phase		1	~
Frequency	f	50/60	Hz
Speed	n	945	RPM
Power consumption	P _e	800	W
Nominal current	I _{nom}	5.8	A
Maximum current	I _{max}	6.4	A
Cos φ		0.6	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		58.3	Lbs.
Packing dimensions		41.7x40.6x7.5	inch

Fan details


Impeller blades	3
Impeller type	8
Impeller system	G
Impeller material	PG

Control options


Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg 12100 CFM
0.20 in. wg 9950 CFM



Speed control diagram



Please note: Picture may deviate from original product

Approval(s)



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com


Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram


BQ06 - 1 Phase - MFD33S + cables + 1x connbox 10-0/0-10V - -

Analogue input signal	Pink wire connection
10-0V	Pink wire is not connected
0-10V	Pink wire is connected to red

Alarm relay contact	
No Alarm	Brown connected to grey
Alarm	Brown not connected to grey



Dimensions



A01:	36.0 inch
A02:	39.6 inch
A03:	39.6 inch
A04:	37.3 inch
A05:	37.3 inch
A06:	9.7 inch
A07:	37.0 inch
A08:	3.7 inch
A09:	1.6 inch
A10:	0.4 inch