

Technical data

Voltage	U	120	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1610	RPM
Power consumption	P _e	280	W
Nominal current	I _{nom}	2.4	A
Maximum current	I _{max}	2.9	A
Cos φ		0.97	
Capacitor		20/250	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		27.7	Lbs.
Packing dimensions		20.9x20.9x13.6	inch

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics


0.00 in. wg	3240 CFM
0.20 in. wg	2740 CFM



Please note: Picture may deviate from original product

Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions				
				
A01:	16.5 inch			
A02:	20.3 inch			
A03:	20.5 inch			
A10:	0.3 inch			
A11:	14.4 inch			
A12:	1.5 inch			
A13:	8.5 inch			
A14:	12.6 inch			
A15:	12.0 inch			

