



Technical data

Voltage	U	200-230	V
Phase		1	~
Frequency	f	50/60	Hz
Speed	n	1415	RPM
Power consumption	P _e	230	W
Nominal current	I _{nom}	1.8	A
Maximum current	I _{max}	2.1	A
Cos φ		0.56	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	64	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	53	dB(A)
Weight		26.6	Lbs.
Packing dimensions		22.0x22.0x12.4	inch

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options


Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg	2910 CFM
0.20 in. wg	2440 CFM



Speed control diagram



Please note: Picture may deviate from original product

Approval(s)



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com


Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com


Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram

CC03 - 3 Phase - Delta connected + MFD33S --



Dimensions



A01:	12.3 inch
A02:	17.4 inch
A03:	17.4 inch
A04:	15.6 inch
A05:	15.6 inch
A06:	7.6 inch
A07:	13.4 inch
A08:	3.3 inch
A09:	1.4 inch
A10:	0.3 inch