



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1665	RPM
Power consumption	P _e	240	W
Nominal current	I _{nom}	1.1	A
Maximum current	I _{max}	1.6	A
Cos φ		0.99	
Capacitor		3.5/450	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	68	dB(A)
Sound pressure level (7 m)	L _p (calc.)	57	dB(A)
Weight		14.0	kg
Packing dimensions		560x560x315	mm


Fan details

Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics



Please note: Picture may deviate from original product

Approval(s)

Motor approval
cULus



Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A



VOSTERMANS
VENTILATION


Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions



A01:	312 mm
A02:	442.5 mm
A03:	442.5 mm
A04:	395 mm
A05:	395 mm
A06:	192 mm
A07:	340 mm
A08:	84 mm
A09:	36 mm
A10:	7.5 mm

