

Technical data

Voltage	U	120	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1130	RPM
Power consumption	P _e	460	W
Nominal current	I _{nom}	4.2	A
Maximum current	I _{max}	5.6	A
Cos φ		0.96	
Capacitor		56/250	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Weight		26.7	kg
Packing dimensions		825x825x395	mm

Fan details


Impeller blades	3
Impeller type	S
Impeller system	G
Impeller material	PG

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0 Pa	14395 m ³ /h
------	-------------------------




Please note: Picture may deviate from original product



No.c16080

Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions			
		A01:	709 mm
		A03:	830 mm
		A13:	230 mm
		A14:	413 mm
		A29:	29 mm
		A30:	115 mm

