



Technical data

Voltage	U	230	V
Phase	1	~	
Frequency	f	60	Hz
Speed	n	1665	RPM
Power consumption	P _e	240	W
Nominal current	I _{nom}	1.1	A
Maximum current	I _{max}	1.6	A
Cos φ		0.99	
Capacitor		3.5/450	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	68	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	57	dB(A)
Weight		24.5	Lbs.
Packing dimensions		22.0x22.0x12.4	inch

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0.00 in. wg 2940 CFM
0.20 in. wg 2560 CFM



Please note: Picture may deviate from original product

Approval(s)

Motor approval
cULus




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com


Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com




Wiring diagram

C1 - 1 Phase - Standard - CCW

S0000010695A



Dimensions



A01:	16.3 inch
A02:	21.4 inch
A03:	21.4 inch
A04:	19.5 inch
A05:	19.5 inch
A06:	7.6 inch
A07:	17.3 inch
A08:	3.3 inch
A09:	1.4 inch
A10:	0.3 inch