



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	620	RPM
Power consumption	P _e	1800	W
Nominal current	I _{nom}	8.3	A
Maximum current	I _{max}	10.0	A
Cos φ		0.94	
Capacitor		32/400	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		255.4	Lbs.

Fan details



Impeller blades	3
Impeller type	12
Impeller system	B
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics

0.00 in. wg 31000 CFM
0.20 in. wg 26050 CFM




Please note: Picture may deviate from original product



Wiring diagram
C1 - 1 Phase - Standard - CW

S0000010695A



VOSTERMANS
VENTILATION


Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions



A01:	50.3 inch
A02:	60.2 inch
A03:	60.2 inch
A04:	7.0 inch
A05:	0.4 inch
A06:	56.7 inch
A07:	63.0 inch
A08:	69.6 inch