



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	1405	RPM
Power consumption	P _e	210	W
Nominal current	I _{nom}	0.8/0.4	A
Maximum current	I _{max}	0.9/0.5	A
Cos φ		0.69	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	64	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	53	dB(A)
Weight		23.2	Lbs.
Packing dimensions		22.0x22.0x12.4	inch

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	No
Transformer	Yes
Frequency drive	Yes

Characteristics

0.00 in. wg	2910 CFM
0.20 in. wg	2470 CFM



Please note: Picture may deviate from original product


Approval(s)



Wiring diagram
C11 - 3 Phase - Y connection - CCW



Dimensions



A01:	16.3 inch
A02:	21.4 inch
A03:	21.4 inch
A04:	19.5 inch
A05:	19.5 inch
A06:	7.6 inch
A07:	17.3 inch
A08:	3.3 inch
A09:	1.4 inch
A10:	0.3 inch

