



Technical data

Voltage	U	115	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1660	RPM
Power consumption	P _e	390	W
Nominal current	I _{nom}	3.5	A
Maximum current	I _{max}	5.3	A
Cos φ		0.98	
Capacitor		30/250	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	68	dB(A)
Sound pressure level (7 m)	L _p (calc.)	57	dB(A)
Weight		14.8	kg
Packing dimensions		600x600x400	mm


Fan details

Impeller blades	4
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics




Please note: Picture may deviate from original product

Approval(s)



Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions	
	A01: 472 mm
	A02: 587 mm
	A10: 6.5 mm
	A11: 403 mm
	A12: 33 mm
	A13: 220 mm
	A14: 374 mm
	A15: 326 mm
	A70: 520 mm