



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	535	RPM
Power consumption	P _e	1550	W
Nominal current	I _{nom}	5.4/3.2	A
Maximum current	I _{max}	6.5/3.8	A
Cos φ		0.72	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	76	db(A)
Sound pressure level (7 m)	L _p (calc.)	65	db(A)
Weight		83.7	kg
Packing dimensions		1480x475x1480	mm

Fan details


Impeller blades	6
Impeller type	12
Impeller system	B
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics

0 Pa 46200 m³/h
50 Pa 39400 m³/h



Please note: Picture may deviate from original product

Approval(s)




No.15400




Wiring diagram

C11 - 3 Phase - Y connection - CCW



Dimensions



A01:	1375 mm
A09:	295 mm
A12:	96 mm
A19:	1480 mm
A20:	1480 mm
A22:	548 mm
A31:	85 mm