

Technical data

Voltage	U	115	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1120	RPM
Power consumption	P _e	540	W
Nominal current	I _{nom}	4.8	A
Maximum current	I _{max}	7.0	A
Cos φ		0.99	
Capacitor		55/250	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Weight		22.2	kg
Packing dimensions		870x870x395	mm

Fan details


Impeller blades	4
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0 Pa	12100 m ³ /h
50 Pa	10400 m ³ /h



Please note: Picture may deviate from original product


Approval(s)

Motor approval




Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions	
	A01: 712 mm
	A02: 850 mm
	A03: 850 mm
	A04: 790 mm
	A05: 790 mm
	A06: 247 mm
	A07: 740 mm
	A08: 105 mm
	A09: 40 mm
	A10: 10 mm

