



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	1450	RPM
Power consumption	P _e	1650	W
Nominal current	I _{nom}	5.6/3.3	A
Maximum current	I _{max}	6.0/3.5	A
Cos φ		0.73	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	80	dB(A)
Sound pressure level (7 m)	L _p (calc.)	69	dB(A)
Weight		27.4	kg
Packing dimensions		870x870x395	mm

Fan details


Impeller blades	4
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0 Pa	21400 m ³ /h
150 Pa	16500 m ³ /h



Please note: Picture may deviate from original product


Approval(s)



Wiring diagram
C11 - 3 Phase - Y connection - CCW



Dimensions



A01:	712 mm
A02:	850 mm
A03:	850 mm
A04:	790 mm
A05:	790 mm
A06:	247 mm
A07:	740 mm
A08:	105 mm
A09:	40 mm
A10:	10 mm

