

Technical data

Voltage	U	400-480	V
Phase		3	~
Frequency	f	50/60	Hz
Speed	n	595	RPM
Power consumption	P _e	2050	W
Nominal current	I _{nom}	2.8	A
Maximum current	I _{max}	4.3	A
Cos φ		0.93	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		0	
IP Class		IP55	
Sound pressure level (9.8 ft)	L _p (meas.)	76	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	69	dB(A)
Weight		244.7	Lbs.
Packing dimensions		68.9x68.9x49.2	inch

Fan details


Impeller blades	3
Impeller type	12
Impeller system	B
Impeller material	PG

Control options



Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg	37600 CFM
0.20 in. wg	29350 CFM



Speed control diagram



Please note: Picture may deviate from original product

Approval(s)




No.23380



Wiring diagram

CC12 - 3 Phase - Star connected Domel AZ + MFD40T/95T (CW) - CW



Aln	Dig In 1
10 - 0V	Dig In 1 = NC
0 - 10V	Dig In 1 = 24V

