



Technical data

Voltage	U	115	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1130	RPM
Power consumption	P _e	110	W
Nominal current	I _{nom}	1	A
Maximum current	I _{max}	1.5	A
Cos φ		0.99	
Capacitor		12/250	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	60	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	49	dB(A)
Weight		27.0	Lbs.
Packing dimensions		23.6x23.6x15.7	inch

Fan details


Impeller blades	4
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0.00 in. wg	2850 CFM
0.12 in. wg	2320 CFM




Please note: Picture may deviate from original product

Approval(s)

Motor approval
CE **UL**

Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions	
	A01: 18.6 inch
	A02: 23.1 inch
	A10: 0.3 inch
	A11: 15.9 inch
	A12: 1.3 inch
	A13: 8.7 inch
	A14: 14.7 inch
	A15: 12.8 inch
	A70: 20.5 inch