

Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	870	RPM
Power consumption	P _e	910	W
Nominal current	I _{nom}	4	A
Maximum current	I _{max}	5.2	A
Cos φ		1	
Capacitor		24/400	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	77	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	66	dB(A)

Fan details


Impeller blades	3
Impeller type	8
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics

0.00 in. wg 13000 CFM
0.20 in. wg 9950 CFM




Please note: Picture may deviate from original product



Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions			
		A01:	35.9 inch
		A02:	49.1 inch
		A03:	49.1 inch
		A08:	7.2 inch
		A09:	0.3 inch
		A20:	45.4 inch
		A22:	48.7 inch
		A26:	50.6 inch