



Technical data

Voltage	U	120	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1140	RPM
Power consumption	P _e	215	W
Nominal current	I _{nom}	2	A
Maximum current	I _{max}	2.7	A
Cos φ		0.89	
Capacitor		20/250	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	47	db(A)
Sound pressure level (7 m)	L _p (calc.)	36	db(A)
Weight		15.6	kg
Packing dimensions		720x720x400	mm

Fan details

Impeller blades	8
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0 Pa	5200 m ³ /h
------	------------------------




Please note: Picture may deviate from original product

Approval(s)



Wiring diagram
C1 - 1 Phase - Standard - CW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions	
	A01:
	A02:
	A04:
	A05:
	A10:
	A13:
	A14:
	A25:

A01:	420 mm
A02:	650 mm
A04:	18 mm
A05:	30 mm
A10:	8.2 mm
A13:	146 mm
A14:	539 mm
A25:	182 mm

