



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	50	Hz
Speed	n	935	RPM
Power consumption	P _e	500	W
Nominal current	I _{nom}	2.2	A
Maximum current	I _{max}	3.4	A
Cos φ		0.98	
Capacitor		16/400	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	69	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	58	dB(A)
Weight		50.3	Lbs.
Packing dimensions		31.5x31.1x15.6	inch

Fan details

Impeller blades	5
Impeller type	5
Impeller system	G
Impeller material	PG


Control options

Triac controller	Yes
Transformer	Yes
RFREINV7 control	Yes

* This fan is suitable for 1~ frequency control with the Invertek Optidrive type RFREINV7. This Invertek Optidrive RFREINV7 is equipped with a special Vostermans Ventilation BV parameter set. This Invertek Optidrive RFREINV7 is available from Vostermans Ventilation BV.

Characteristics


0.00 in. wg	6770 CFM
0.20 in. wg	5800 CFM



Please note: Picture may deviate from original product

Approval(s)





Wiring diagram

C1 - 1 Phase - Standard - CCW

S0000010695A

