



Technical data

Voltage	U	265/460	V
Phase		3	~
Frequency	f	60	Hz
Speed	n	1135	RPM
Power consumption	P _e	130	W
Nominal current	I _{nom}	0.5/0.3	A
Maximum current	I _{max}	0.6/0.4	A
Cos φ		0.52	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		26.7	Lbs.
Packing dimensions		23.6x23.6x15.7	inch

Fan details


Impeller blades	4
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	No
Transformer	Yes
Frequency drive	No

Characteristics


0.00 in. wg	3120 CFM
0.12 in. wg	2560 CFM



Please note: Picture may deviate from original product




Wiring diagram
C11 - 3 Phase - Y connection - CCW



Article number: T6D45NAM80100

Circulation fans

Dimensions			
			
A01:	18.6 inch		
A02:	23.1 inch		
A10:	0.3 inch		
A11:	15.9 inch		
A12:	1.3 inch		
A13:	8.7 inch		
A14:	14.7 inch		
A15:	12.8 inch		
A70:	20.5 inch		