



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	965	RPM
Power consumption	P _e	530	W
Nominal current	I _{nom}	2.3/1.3	A
Maximum current	I _{max}	2.7/1.6	A
Cos φ		0.59	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	70	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	59	dB(A)
Weight		53.3	Lbs.
Packing dimensions		31.5x31.1x15.6	inch

Fan details


Impeller blades	5
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg 6940 CFM
0.20 in. wg 6120 CFM



Please note: Picture may deviate from original product

Approval(s)




Wiring diagram
C11 - 3 Phase - Y connection - CCW



Article number: V6T63AAE10100

Panel fans

Dimensions



A01:	25.4 inch
A02:	30.5 inch
A03:	30.5 inch
A04:	28.1 inch
A05:	28.1 inch
A06:	9.7 inch
A07:	26.4 inch
A08:	4.1 inch
A09:	1.6 inch
A10:	0.4 inch



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com