



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1100	RPM
Power consumption	P _e	610	W
Nominal current	I _{nom}	2.7	A
Maximum current	I _{max}	3.5	A
Cos φ		1	
Capacitor		14/400	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Weight		24.4	kg
Packing dimensions		870x870x395	mm

Fan details


Impeller blades	4
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0 Pa	13400 m ³ /h
50 Pa	11500 m ³ /h



Please note: Picture may deviate from original product

Approval(s)

Motor approval
cULus




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com


Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com



Wiring diagram

C1 - 1 Phase - Standard - CCW

S0000010695A



Dimensions

