



Technical data

Voltage	U	200-230	V
Phase		1	~
Frequency	f	50/60	Hz
Speed	n	365	RPM
Power consumption	P _e	855	W
Nominal current	I _{nom}	6.7	A
Maximum current	I _{max}	7.4	A
Cos φ		0.61	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	66	dB(A)
Sound pressure level (7 m)	L _p (calc.)	55	dB(A)
Weight		29.9	kg

Fan details

Impeller blades	3
Impeller type	10
Impeller system	N
Impeller material	PG



Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0 Pa 41800 m³/h

Speed control diagram




Please note: Picture may deviate from original product

Approval(s)



Dimensions



A01:	1524 mm
A03:	1810 mm
A04:	1180 mm
A10:	15 mm
A13:	339 mm
A14:	536 mm



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com