



Technical data

Voltage	U	265/460	V
Phase		3	~
Frequency	f	60	Hz
Speed	n	1160	RPM
Power consumption	P _e	1800	W
Nominal current	I _{nom}	5.8/3.3	A
Maximum current	I _{max}	6.8/3.9	A
Cos φ		0.68	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		92.6	Lbs.
Packing dimensions		47.2x47.2x19.7	inch

Fan details


Impeller blades	4
Impeller type	8
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg 18000 CFM
0.40 in. wg 15050 CFM



Please note: Picture may deviate from original product

Approval(s)

Motor approval
cULus

EAC



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com


Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram
C11 - 3 Phase - Y connection - CCW



Dimensions



A01:	35.8 inch
A03:	47.4 inch
A07:	38.8 inch
A08:	8.3 inch
A10:	0.4 inch
A14:	20.1 inch