



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	980	RPM
Power consumption	P _e	2100	W
Nominal current	I _{nom}	7.8/4.5	A
Maximum current	I _{max}	9.1/5.3	A
Cos φ		0.68	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-4...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Weight		133.9	Lbs.

Fan details


Impeller blades	8
Impeller type	8
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0.00 in. wg 16600 CFM
0.60 in. wg 14000 CFM



Please note: Picture may deviate from original product

Approval(s)



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com


Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram

BB07 - 3 Phase - Star Connected Rotor - CCW



Dimensions




Fig. 2

A01:	35.4 inch
A03:	43.9 inch
A06:	5.2 inch
A07:	36.7 inch
A08:	3.5 inch
A10:	0.4 inch
A14:	16.2 inch