



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	50	Hz
Speed	n	1410	RPM
Power consumption	P _e	180	W
Nominal current	I _{nom}	0.9	A
Maximum current	I _{max}	1.5	A
Cos φ		0.92	
Capacitor		3.5/450	μF/V
Ambient temperature	T _{amb min/max}	-13...104	°F
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (6.6 ft)	L _p (meas.)	63	dB(A)
Sound pressure level (23 ft)	L _p (calc.)	53	dB(A)
Weight		30.2	Lbs.
Packing dimensions		22.0x22.0x12.4	inch

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0.00 in. wg 2710 CFM
0.20 in. wg 2270 CFM




Please note: Picture may deviate from original product


Approval(s)



Wiring diagram
C1 - 1 Phase - Standard - CCW



Dimensions



A01:	16.3 inch
A02:	21.4 inch
A03:	21.4 inch
A04:	19.5 inch
A05:	19.5 inch
A06:	7.6 inch
A07:	17.3 inch
A08:	3.3 inch
A09:	1.4 inch
A10:	0.3 inch