



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	50	Hz
Speed	n	1420	RPM
Power consumption	P _e	260	W
Nominal current	I _{nom}	1.2	A
Maximum current	I _{max}	1.8	A
Cos φ		1	
Capacitor		05/400	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	64	dB(A)
Sound pressure level (7 m)	L _p (calc.)	53	dB(A)
Weight		13.4	kg
Packing dimensions		635x635x360	mm

Fan details

Impeller blades	3
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics

0 Pa	5050 m ³ /h
------	------------------------




Please note: Picture may deviate from original product

Approval(s)



Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A




VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions			
		A01:	512 mm
		A03:	575 mm
		A13:	174 mm
		A14:	332 mm
		A29:	34 mm
		A30:	115 mm

