Article number: V4D56AAM10100

Panel fans

Multifan

Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	1455	RPM
Power consumption	P_e	900	W
Nominal current	I_{nom}	3.4/2	A
Maximum current	I_{max}	3.6/2.1	A
Cos ϕ		0.66	
Capacitor		-	µF/V
Ambient temperature	$T_{amb\ min/max}$	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	$L_{p\ (meas.)}$	76	dB(A)
Sound pressure level (7 m)	$L_{p\ (calc.)}$	65	dB(A)
Weight		21.2	kg
Packing dimensions		720x720x400	mm

Fan details

Impeller blades	4
Impeller type	5
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0 Pa	12700 m^3/h
100 Pa	10600 m^3/h



Please note: Picture may deviate from original product

Approval(s)

CE EAC

ErP 2026 COMPLIANT

VOSTERMANS VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Version 3.0 23Oct2025

Article number: V4D56AAM10100

Panel fans

Wiring diagram

C11 - 3 Phase - Y connection - CCW



Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Article number: V4D56AAM10100

Panel fans

Dimensions



A01:	574 mm
A02:	700 mm
A03:	700 mm
A04:	640 mm
A05:	640 mm
A06:	247 mm
A07:	600 mm
A08:	105 mm
A09:	40 mm
A10:	10 mm

Data according to commission Regulation (EU) 327/2011

Axial fan efficiency	ηf	40.5%
Measurement category		A
Efficiency category		Static
Efficiency grade	N	47
VSD		Not included
Year of manufacturing		
Manufacturer		VOSTERMANS Parlevinkerweg 54 5928 NV Venlo The Netherlands
Commercial reg. no.		12021767
Model number		V4D56AAM10100
Motor input power	Pe	1.003 kW
Volume flow	Qv	8303 m³/h
Pressure difference	psf	176 Pa
Rotational speed	n	1449 rpm
Specific ratio		1.02

Data at optimum energy efficiency point

Consult instructions for information regarding installation, disassembly and recycling of this product

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com