

Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1150	RPM
Power consumption	P _e	180	W
Nominal current	I _{nom}	0.8	A
Maximum current	I _{max}	1.2	A
Cos φ		0.96	
Capacitor		05/400	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Weight		13.8	kg
Packing dimensions		600x600x400	mm


Fan details

Impeller blades	4
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics



Please note: Picture may deviate from original product


Approval(s)

Motor approval




Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A



VOSTERMANS
VENTILATION


Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Dimensions



A01:	472 mm
A02:	587 mm
A10:	6.5 mm
A11:	403 mm
A12:	33 mm
A13:	220 mm
A14:	374 mm
A15:	326 mm
A70:	520 mm

