



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	1450	RPM
Power consumption	P _e	1650	W
Nominal current	I _{nom}	5.7/3.3	A
Maximum current	I _{max}	6.5/3.8	A
Cos φ		0.73	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Weight		25.8	kg
Packing dimensions		1100x900x530	mm

Fan details


Impeller blades	6
Impeller type	S
Impeller system	G
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	Yes

Characteristics

0 Pa	19100 m ³ /h
150 Pa	16100 m ³ /h



Please note: Picture may deviate from original product


Approval(s)



Wiring diagram
C11 - 3 Phase - Y connection - CCW



Dimensions



A01:	640 mm
A03:	866 mm
A07:	715 mm
A08:	210 mm
A10:	9 mm
A14:	410 mm

Data according to commission Regulation (EU) 327/2011

Axial fan efficiency	η_f	41.6%
Measurement category		D
Efficiency category		Static
Efficiency grade	N	46
VSD		Not included
Year of manufacturing		
Manufacturer		VOSTERMANS Parlevinkerweg 54 5928 NV Venlo The Netherlands 12021767
Commercial reg. no.		H4D6302M10100
Model number		2.004 kW
Motor input power	Pe	12519 m ³ /h
Volume flow	Qv	240 Pa
Pressure difference	psf	1438 rpm
Rotational speed	n	1.02
Specific ratio		

Data at optimum energy efficiency point

Consult instructions for information regarding installation, disassembly and recycling of this product