



Technical data

Voltage	U	230	V
Phase		1	~
Frequency	f	60	Hz
Speed	n	1130	RPM
Power consumption	P _e	110	W
Nominal current	I _{nom}	0.5	A
Maximum current	I _{max}	0.8	A
Cos φ		0.99	
Capacitor		03/400	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	60	dB(A)
Sound pressure level (7 m)	L _p (calc.)	49	dB(A)
Weight		12.1	kg
Packing dimensions		600x600x400	mm


Fan details

Impeller blades	4
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	No

Characteristics



Please note: Picture may deviate from original product


Approval(s)

Motor approval
cULus



Wiring diagram
C1 - 1 Phase - Standard - CCW

S0000010695A



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com


Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Article number: T6E45NAM80100

Circulation fans

Dimensions			
			
A01:	472 mm		
A02:	587 mm		
A10:	6.5 mm		
A11:	403 mm		
A12:	33 mm		
A13:	220 mm		
A14:	374 mm		
A15:	326 mm		
A70:	520 mm		