



Technical data

Voltage	U	230/400	V
Phase		3	~
Frequency	f	50	Hz
Speed	n	555	RPM
Power consumption	P _e	1500	W
Nominal current	I _{nom}	5.3/3.1	A
Maximum current	I _{max}	6.2/3.6	A
Cos φ		0.71	
Capacitor		-	μF/V
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class		IP55	
Sound pressure level (2 m)	L _p (meas.)	75	dB(A)
Sound pressure level (7 m)	L _p (calc.)	64	dB(A)
Weight		126.1	kg
Packing dimensions		2590x1000x1000	mm



Fan details

Impeller blades	3
Impeller type	12
Impeller system	B
Impeller material	PG

Control options

Triac controller	No
Transformer	No
Frequency drive	No

Characteristics



Please note: Picture may deviate from original product

Approval(s)



No.15447



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com

Wiring diagram
C11 - 3 Phase - Y connection - CW



Article number: C4D14A3M10241

FC fans - High volume

Dimensions

A technical drawing of the front view of a circular ventilation unit. It shows a circular grille with a central hub and radial vanes. Dimension A01 is the radius from the center to the outer edge of the grille. Dimension A02 is the total diameter of the unit. Dimension A03 is the height of the unit, which is equal to its diameter.

A technical drawing of the side view of the ventilation unit. It shows the profile of the unit, including the grille and the internal structure. Dimension A08 is the thickness of the grille. Dimension A09 is the thickness of the unit. Dimension A20 is the diameter of the central hub. Dimension A22 is the total diameter of the unit. Dimension A26 is the height of the unit, which is equal to its diameter.

A01:	1369 mm
A02:	1710 mm
A03:	1710 mm
A08:	179 mm
A09:	10 mm
A20:	1621 mm
A22:	1650 mm
A26:	1874 mm

 **VOSTERMANS**
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com